

SurfaPore



R



Water Repellent for:

- Clay-based Surfaces
- Ceramic Roof Tiles
- Cotto Tiles
- Pottery

Water Based
Without Hazardous Solvents

SurfaPore R

Nanotechnology for any clay based surface such as roof tiles, cotto and pottery.

SurfaPore R protects your clay surfaces from water penetration. Ceramics and roof tiles are effectively protected from deterioration and from the unsightly "greening" of mould growth.

SurfaPore R preserves the aesthetics of your clay surfaces while protecting them against water and ageing. Due to their unique nature, SurfaPore R was designed to exactly "fit" the structural and surface properties of clay based materials. After applying SurfaPore R, your clay surfaces repel water and can remain dry even after rain! Protect your roof tops and favourite clay based surfaces from "greening" and getting mouldy!

Application. Surface Application: The application surface should be dry and clean. Apply SurfaPore R by using a brush, a roller or spraying. No dilution is required. On very absorptive surfaces re-apply within 3 hours.

Dipping: Dip the clay based surface in SurfaPore R for 30 seconds. In any case (surface application or mixing) test results on a small area before full scale application.

Maximum water repellency is achieved 24 hours post application. **Consumption:** Estimated consumption rate 9-11 m²/L, strongly dependant on the properties of the surface applied. **Production Date:** See packaging.

Properties: Milky white water emulsion. Does not change the appearance of the surface applied. The product must not freeze. Can be stored in its original, sealed container for 24 months after production date. **Safety:** SurfaPore R is a non hazardous product but as a precaution avoid contact with skin or eyes and wear protective gloves and goggles. Dispose this material properly. Keep out of the reach of children. In case of contact with eyes or skin, rinse immediately with plenty of water and seek medical advice. Always request, read and comprehend the Material Safety Data Sheet of the product before application.

Made in the EU. SurfaPore logo is a registered trademark of NanoPhos SA.

VOC (Volatile Organic Compounds) Maximum EU VOC content limit value (Directive 2004/42/CE) of the product in a ready to use condition (category A/c "coatings for exterior walls of mineral substrate", Type WB): 75 g/L (2007), 40 g/L (2010). **Maximum VOC content of this product is 20 g/L.**

NanoPhos
Pioneering
Nanotechnology



Produced by:
NanoPhos SA
Sci. & Technology Park
Lavrio 19500
Greece

1 Litre e

Tel. (+30) 22920 69312
www.NanoPhos.com

UK & Ireland Exclusive Distributor: Nanotech Solutions Ltd., 6 Greens Close, Bedfordshire SG19 1AD, UK
Tel/Fax: 01767 680946, www.nanotecholutions.uk.com



5 200351 100892 >